



APPLICATIONS

- Ideal for potable water applications, providing efficient performance with floating stage hydraulics

FEATURES

- Designed for use in 4" and greater diameter water well applications
- Eight performance ranges: 5, 8, 10, 12, 16, 18, 22 or 26 GPM
- Horsepower ranges: 1/2 to 5
- Stainless steel components are 300 series grade or better
- 1.25" NPT discharge pipe connection with sufficient wrench flat area allows for quick and easy installation
- Stainless steel connection pumps are equipped with a wafer disc-style check valve
- Powered by corrosion-resistant super stainless 4-inch submersible motors with lightning protection
- Max water temperature with the proper flow is 49 °C.
- NSF/ANSI 61 Certified

4-Inch Encapsulated Motor



APPLICATIONS

- These motors are built for dependable operation in 4" diameter or larger water wells

FEATURES

- Single-phase Voltage 230 V 60 Hz, 220 V 50 Hz
- Three-phase Voltages 200 V, 230 V, 380 V, 575 V 60 Hz, 460/380 V 60/50 Hz
- Corrosion-Resistant Construction
- Water Lubrication
- Filter Check Valve (Water Well)
- Kingsbury-type Thrust Bearing
- Built-in Lightning Arrestors (single-phase)
- UL 778 Recognized (North American Voltages)
- CSA C22.2 #108 Certified
- Sand Fighter Slinger
- NSF/ANSI 61 Certified