

INLINE AND CONTROL



Economical. Reliable. Compatible.

Inline Controls Compatibility with FPS Pumps



franklinwater.com



INLINE		FLW	SWC	SWP	ADJ 115V	ADJ 230V	CTL
		91987102	91987103	91987104	91987105	91987106	91987107
Operating Conditions	Motor Size	Up to 1.5 hp	Up to 2 hp	Up to 3 hp	Up to 0.75 hp	Up to 2 hp	Up to 3 hp
	Max Current	15 A	16 A	20 A	16 A	16 A	20 A
	Voltage	115/230V	115/230V	115/230V	115V	230V	115/230V
	Thread (In.)	1" MNPT	1" MNPT	1.25" MNPT	1" MNPT	1" MNPT	1.25" MNPT
	Max. Temperature	150 °F	150 °F	150 °F	150 °F	150 °F	150 °F
Features	Flow Based Pump Activation	✓	✓	✓	✓	✓	✓
	Run Dry Protection	✓	✓	✓	✓	✓	✓
	Low-Pressure Backup Activation		✓	✓	✓	✓	✓
	Replaces Pressure Switch and Tank	✓	✓	✓	✓	✓	✓
	Positive Suction Lift		✓	✓	✓	✓	✓
	Includes Pressure Gauge				✓	✓	✓
	Adj. Low-Pressure Backup Activation				✓	✓	
	Maximum Pressure Regulation						✓

Proper pump selection is essential for use with the Inline FLW, SWC, SWP, and ADJ as pump shut-off pressure will be realized within the system prior to shut down. If the pump size can not be reduced, select the Inline CTL with built-in pressure reducing valve.

FEATURES & BENEFITS

Specifically built for water pumping applications, Franklin Electric's Inline Controls include five pump starting and control devices that pair with a variety of submersible or surface pumps up to 20 amps (or approximately 3 hp) to provide or boost the system's overall water pressure – and in most cases, without the need of an additional bladder tank.

They also offer two unique features that ensure the system remains functional and hassle free, including a daily motor rotation start designed to energize the motor at least once every 24 hours to prevent system locking, and a unique automatic restart feature eliminating the need to manually restart the pump in the case of an unexpected trip or fault.

- **Less Equipment:** Eliminates the need for a bladder tank and pressure switch
- **Simplified Installation:** Reduces time, labor and the need for heavy equipment in applications where a buried tank would have been used
- **Built-in Control:** Allows pump to start automatically, on-demand
- **Automatic Restart Feature:** Eliminates the need to manually activate the pump after a system fault
- **System Reliability:** Built-in pump dry-run protection, check valve, and dead-head prevention
- **Fully Supported:** Comes fully supported by the industry's leading Technical Support professionals and Field Service Engineers

CISTERN PUMPS & SHALLOW WELL JET PUMPS

PUMP COMPATIBILITY			PUMP SPECIFICATIONS				INLINE CONTROLS					
Pump Series	Model	Order No.	Volts	Amps	Shut-off Pressure (ft)	Recommended Max (ft)	FLW 91987102	SWC 91987103	SWP 91987104	ADJ 115V 91987105	ADJ 230V 91987106	CTL 91987107
 C1	10C1-05P4-2W115	90301005	115	10	224	204	✓	✓	✓*	✓		✓*
	10C1-05P4-2W230	90301010	230	5	224	204	✓	✓	✓*		✓	✓*
	20C1-05P4-2W115	90302005	115	10	140	125	✓	✓	✓*	✓		
	20C1-05P4-2W230	90302010	230	5	140	125	✓	✓	✓*		✓	
	20XC1-05P4-2W115	90302015	115	10	164	148	✓	✓	✓*	✓		
	20XC1-05P4-2W230	90302020	230	5	164	148	✓	✓	✓*		✓	
 SWJ (Cyclone)	FSWJ05P	91090005	115	12.4	131	127		✓	✓*	✓		
			230	6.2	131	127		✓	✓*		✓	
	FSWJ07P	91090007	115	14.8	145	138		✓	✓*	✓		
			230	7.4	145	138		✓	✓*		✓	
	FSWJ10P	91093010	115	13	152	138		✓	✓*	✓		
			230	6.7	152	138		✓	✓*		✓	
 Versajet	FVJ05CI	91180005	115	9.4	161	138		✓	✓*	✓		
			230	4.7	161	138		✓	✓*		✓	
	FVJ07CI	91180007	115	12.4	161	138		✓	✓*	✓		
			230	6.2	161	138		✓	✓*		✓	
	FVJ1CI	91180010	115	14.8	147	138		✓	✓*	✓		
			230	7.4	147	138		✓	✓*		✓	
 Versajet Pro	FVJ05CI-P	91181005	115	12.4	161	138		✓	✓*	✓		
			230	6.2	161	138		✓	✓*		✓	
	FVJ07CI-P	91181007	115	14.8	147	138		✓	✓*	✓		
			230	7.4	147	138		✓	✓*		✓	
	FVJ1CI-P	91181010	115	19.9	152	138			✓*			
			230	9.95	152	138			✓*			

NOTE: All pumps have a 1" discharge | * Device thread is a larger size than pump discharge (requires reducer coupling)

MULTI-STAGE & HIGH PERFORMANCE BOOSTER PUMPS

PUMP COMPATIBILITY			PUMP SPECIFICATIONS				INLINE CONTROLS					
Pump Series	Model	Order No.	Volts	Amps	Shut-off Pressure (ft)	Recommended Max (ft)	FLW 91987102	SWC 91987103	SWP 91987104	ADJ 115V 91987105	ADJ 230V 91987106	CTL 91987107
 BT4	5FBT05S4	95830510	115	12.4	360	350		✓	✓*	✓		✓*
			230	6.2	360	350	✓	✓	✓*		✓	✓*
	7FBT05S4	95830710	115	12.4	340	320	✓	✓	✓*	✓		✓*
			230	6.2	340	320	✓	✓	✓*		✓	✓*
	7FBT07S4	95830715	115	14.8	420	400	✓	✓	✓*	✓		✓*
			230	7.4	420	400	✓	✓	✓*		✓	✓*
	10FBT05S4	95831010	115	12.4	290	270	✓	✓	✓*	✓		✓*
			230	6.2	290	270	✓	✓	✓*		✓	✓*
	10FBT07S4	95831015	115	14.8	340	310	✓	✓	✓*	✓		✓*
			230	7.4	340	310	✓	✓	✓*		✓	✓*
	15FBT07S4	95831515	115	14.8	260	240	✓	✓	✓*	✓		✓*
			230	7.4	260	240	✓	✓	✓*		✓	✓*
	15FBT1S4	95831520	115	19.9	350	325			✓*			✓*
			230	9.95	350	325	✓	✓	✓*		✓	✓*
	20FBT07S4	95832015	115	14.8	180	175			✓*			✓*
			230	7.4	180	175			✓*			✓*
 MH	15FMH05S2	96061500	115	9.4	101	85	✓	✓	✓*	✓		
			230	4.7	101	85	✓	✓	✓*		✓	
	15FMH07S3	96061501	115	12.4	152	135	✓	✓	✓*	✓		
			230	6.2	152	135	✓	✓	✓*		✓	
	15FMH1S4	96061502	115	14.8	203	180	✓	✓	✓*	✓		✓*
			230	7.4	203	180	✓	✓	✓*		✓	✓*
	15FMH1S5	96061503	115	19.9	256	235			✓*			✓*
			230	9.95	256	235	✓	✓	✓*		✓	✓*
	15FMH2S6	96061504	230	12	311	285		✓	✓*		✓	✓*
								✓	✓*		✓	✓*

NOTE: All pumps have a 1" discharge | * Device thread is a larger size than pump discharge (requires reducer coupling)

INLINE

CONVERTIBLE JET PUMPS (WITH SHALLOW WELL INJECTOR)

PUMP COMPATIBILITY			PUMP SPECIFICATIONS				INLINE CONTROLS					
Pump Series	Model	Order No.	Volts	Amps	Shut-off Pressure (ft)	Recommended Max (ft)	FLW 91987102	SWC 91987103	SWP 91987104	ADJ 115V 91987105	ADJ 230V 91987106	CTL 91987107
	FCVJ05CI	Multiple	115	9.4	122	161		✓	✓*	✓		
			230	4.7	122	161		✓	✓*		✓	
	FCVJ07CI	Multiple	115	12.4	136	161		✓	✓*	✓		
			230	6.2	136	161		✓	✓*		✓	
	FCVJ10CI	Multiple	115	14.8	136	161		✓	✓*	✓		
			230	7.4	136	161		✓	✓*		✓	
	FCVJ05CI-P	Multiple	115	12.4	136	161		✓	✓*	✓		
			230	6.2	136	161		✓	✓*		✓	
	FCVJ07CI-P	Multiple	115	14.8	136	184		✓	✓*	✓		
			230	7.4	136	184		✓	✓*		✓	
	FCVJ10CI-P	Multiple	115	19.9	164	184		✓	✓*			
			230	9.95	164	184		✓	✓*		✓	
	FP05CI-C	91140005	115	11.8	109	103		✓	✓*	✓		
			230	5.9	109	103		✓	✓*		✓	
	FP07CI-C	91140007	115	14.8	119	127		✓	✓*	✓		
			230	7.4	119	127		✓	✓*		✓	
	FP1CI-C	91140010	115	14.4	147	150		✓	✓*	✓		
			230	7.7	147	150		✓	✓*		✓	
	FE05CI-C	91060020	115	9.4	127	127		✓	✓*	✓		
			230	4.8	127	127		✓	✓*		✓	
	FE07CI-C	91060053	115	12.8	120	127		✓	✓*	✓		
			230	6.4	120	127		✓	✓*		✓	

NOTE: All pumps have a 1" discharge | * Device thread is a larger size than pump discharge (requires reducer coupling)

CONVERTIBLE JET PUMPS (WITH DEEP WELL INJECTOR)

PUMP COMPATIBILITY			PUMP SPECIFICATIONS				INLINE CONTROLS					
Pump Series	Model	Order No.	Volts	Amps	Shut-off Pressure (ft)	Recommended Max (ft)	FLW 91987102	SWC 91987103	SWP 91987104	ADJ 115V 91987105	ADJ 230V 91987106	CTL 91987107
Convertible VersaJet	FCVJ15CI	Multiple	115	19.9	120	127			✓*			
			230	9.95	120	127		✓	✓*		✓	
Convertible VersaJet Pro	FCVJ10CI-P	Multiple	115	19.9	120	127			✓*			
			230	9.95	120	127		✓	✓*		✓	
Con. Pro (RM2)	FP05CI-C	91140005	115	11.8	120	127		✓	✓*	✓		
			230	5.9	120	127		✓	✓*		✓	
	FP07CI-C	91140007	115	14.8	122	150		✓	✓*	✓		
			230	7.4	122	150		✓	✓*		✓	
	FP1CI-C	91140010	115	14.4	136	150		✓	✓*	✓		
			230	7.7	136	150		✓	✓*		✓	
C Series	FE05CI-C	91060020	115	9.4	120	115		✓	✓*	✓		
			230	4.8	120	115		✓	✓*		✓	
	FE07CI-C	91060053	115	12.8	115	115		✓	✓*	✓		
			230	6.4	115	115		✓	✓*		✓	

NOTE: All pumps have a 1" discharge | * Device thread is a larger size than pump discharge (requires reducer coupling)

TRANSFER PUMPS

PUMP COMPATIBILITY			PUMP SPECIFICATIONS				INLINE CONTROLS					
Pump Series	Model	Order No.	Volts	Amps	Shut-off Pressure (ft)	Recommended Max (ft)	FLW 91987102	SWC 91987103	SWP 91987104	ADJ 115V 91987105	ADJ 230V 91987106	CTL 91987107
	5FPD51-S	93178056	115	12	74	70	✓					
			230	6	74	70	✓					

NOTE: All pumps have a 1" discharge